

Technical Data Sheet


SM 2576 P

Description	Print	Applications
SM **76 P are two Fogra certified resin coated media with semi matt finish. Available as SM 2076 P and SM 2576 P.	universally printable with all common > dye inks > pigmented inks > latex inks suitable for HP Indigo	> designed for contract proofs and professional color management applications > products are approved by Fogra as semi matt proofing papers. > used for small format and large format prints

Properties	Value	Unit	Test Method
Substance	255 ± 10	g/sqm	ISO 536
Thickness	267 ± 12	µm	ISO 534
Opacity	96 ± 3	%	ISO 2471
Stiffness md	65 ± 5	mN	ISO 2493
Stiffness cd	40 ± 5	mN	ISO 2493
Gloss value 60° (fs)	17 ± 4	%	ISO 2813
Smoothness (fs)	> 1000	sec	ISO 5627
CIE (Whiteness (fs)	99 ± 4		ISO 11475
Shade (D50/2°) (fs) L*	96.5 ± 1.5		ISO 5631-2
a*	0.0 ± 0.8		ISO 5631-2
b*	-1.5 ± 0.8		ISO 5631-2

Availabilities	Certificates
Sheets	> ISO 9001
Plotter roll sizes	> ISO 14001
Standard jumbo roll length	> ISO 50001
High Speed inkjet	> Fogra
Sample roll size	

Additional sizes and dimensions on request

Best printing results achieved in a standard climate of 23°C and 50% relative humidity. For problem-free running, always store the product in original packaging and protect it from direct sunlight and moisture. Before using our medium, check its suitability on your printer and for your planned application. We can assume no liability resulting from technical changes in printers and/or inks. Changes in the product design due to technical further developments will not be announced in advance.

March 2016, subject to alterations